




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : E21B 19/22, B66D 3/00, E02D 1/02</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/17481</p> <p>(43) International Publication Date: 30 March 2000 (30.03.00)</p>
<p>(21) International Application Number: PCT/NL99/00596</p> <p>(22) International Filing Date: 24 September 1999 (24.09.99)</p> <p>(30) Priority Data: 1010179 24 September 1998 (24.09.98) NL</p> <p>(71) Applicant (for all designated States except US): HY-DRO-NAUTIC SERVICES [NL/NL]; Driftstraat 63, NL-2315 CD Leiden (NL).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): VAN DE MEIDE, Hans [NL/NL]; Driftstraat 63, NL-2315 CD Leiden (NL).</p> <p>(74) Agent: 'T JONG, Bastiaan, Jacobus; Arnold & Siedsma, Sweelinckplein 1, NL-2517 GK The Hague (NL).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. In English translation (filed in Dutch).</p>

(54) Title: INJECTOR USED FOR TUBING OR COILED TUBING



(57) Abstract

Device for driving a rigid elongate element such as a rod or tube in its longitudinal direction, comprising a frame, at least two engaging systems arranged on the frame which each comprise an endless flexible member provided with engaging elements and guide means for guiding each of the endless members, wherein the guide means of each system are arranged such that they define a part of the endless flexible member in which the engaging elements co-act with those in a corresponding co-acting part of another system, and drive means for driving at least one of the endless members.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INJECTOR USED FOR TUBING OR COILED TUBING

The invention relates to a device for driving in its longitudinal direction, i.e. moving by pulling or pushing, a rigid elongate element such as a rod or tube. Such a device is applied for instance in soil analysis. A probe is then fixed to an end of the rod or tube and driven into the ground using the device. During driving into the ground the encountered resistance is measured by the probe and transmitted to a recording device. The nature of the ground can thus be established and it can for instance be determined at which depth in the ground good bearing layers are situated.

In known devices of this type the elongate element is assembled from separate pipe parts. These are driven into the ground using a hydraulic jack. When one pipe part has been driven into the ground, a subsequent pipe part is screwed on top thereof and the driving-in operation can be repeated. This continues thus until the assembled pipe has been driven to the desired depth into the ground. Removal takes place in reverse manner.

The use of separate pipe elements makes use of the device time-consuming. Devices are indeed known for obviating this drawback wherein use is made of a rigid elongate element such as a rod or tube in one piece, which is wound onto a large diameter. Driving of this elongate element into the ground takes place with wheel sets, which engage on both sides of the elongate element and drive it clampingly therebetween. The pressure on the elongate element must be great to enable sufficient force to be produced. This entails the drawback of a heavy and bulky construction to be able to absorb the forces to be generated, as well as the danger of damage to the rigid elongate element.

The invention has for its object to provide a device of the type stated in the preamble which can be embodied compactly and with which a rigid elongate

element such as a rod or tube can be driven in its longitudinal direction in reliable manner.

This objective is achieved in the device according to the invention as characterized in claim 1.

5 The engagement on the elongate element by the engaging elements takes place over a considerable length, so that the contact pressure can remain limited. The device can hereby take a light and compact form, while the risk of the deformation of the rod or tube is extremely small.

10 The force on the elongate element can be dosed precisely by applying the measure of claim 2.

Both measures of claim 3 are preferably applied. The means by which the force is generated for operation of the engaging systems can herein be separated
15 from those with which the elongate element is driven, thus enabling an effective construction of the device.

A simple embodiment is characterized in claim 4. According to a further development the measure of claim 5 is applied. Via the guide rollers a considerable
20 force can be exerted on the parts of the endless flexible members without this entailing considerable frictional losses.

An advantageous further development is herein characterized in claim 6. By incorporating the guide
25 rollers in a circuit, these do not have to be separately mounted, so that a construction is obtained which is simpler and less susceptible to malfunction.

In order to obtain a good engagement of the engaging elements on the rigid elongate element, the
30 measure of claim 7 is preferably applied. The recesses can herein be dimensioned such that they fit closely onto the rigid elongate element, whereby a good clamping and driving-engagement is obtained.

In order to enhance the engagement the measure
35 of claim 8 is advantageously applied.

A suitable embodiment is characterized in claim 9. The chain can transmit considerable forces and forms herein a good means for mounting the engaging elements.

The flexible member is herein embodied in suitable manner with two chains situated mutually adjacently at a distance, wherein the engaging elements are arranged between these chains. The urging means can then engage on the engaging elements in simple manner without the force having to be transmitted via the flexible member.

The invention will be further elucidated in the following description with reference to the annexed figures, in which embodiments are shown.

Fig. 1 shows a partly broken away perspective view of a device according to a preferred embodiment of the invention;

fig. 2 shows a partly broken away perspective detail view as according to arrow II in fig. 1;

fig. 3 shows a view partly corresponding with fig. 2 of an alternative embodiment;

fig. 4 and 5 show different embodiment variants of chains as used in preferred embodiments of the invention;

fig. 6 shows a schematic side view of a device according to the invention in the situation of use.

The device 1 shown in fig. 1 comprises a main frame 2 in which two sub-frames 3 and 4 are moveably enclosed. These sub-frames 3, 4 can be moved toward and away from each other using hydraulic cylinders 6 which are connected on one side to frame 2 and on the other to one of the sub-frames 3, 4.

Each sub-frame 3, 4 comprises an engaging system 5 which each comprise an endless flexible member in the form of a double chain 8 provided with engaging elements 11. Each double chain 8 is trained round a number of chain wheels 9 such that a vertical part is defined in each case between two chain wheels situated one above the other.

These corresponding vertical parts of sub-frames 3, 4 lie opposite each other such that the engaging elements 11 thereof can co-act for clamping

therebetween of a rigid elongate element 7 in the form of a long rod or tube. Connected to one of the chain wheels 9 in each case is a drive 10 which can drive the assembly of chains 8 and engaging elements 11 such that engaging elements 11 are moved downward respectively upward in the vertical parts. Because engaging elements 11 therein engage the rod or tube 7, this latter is herein driven vertically upward or downward.

Device 1 is further provided with urging means 12 which can urge toward each other the co-acting vertical parts of chains 8 and the engaging elements connected thereto. These urging means 12 comprise pressure plates 13 on both sides of the vertical chain parts which are mutually coupled by means of hydraulic cylinders 12 on either side. By feeding hydraulic cylinders 12 with hydraulic oil under pressure such that the piston rod in the cylinder is pulled inward, pressure blocks 13 are urged toward each other and the chain parts and engaging elements 11 are herein also urged toward each other, therein firmly clamping rod or tube 7. For release of the urging means cylinders 12 are loaded in the opposite direction, whereby the pressure on the parts is removed. Sub-frames 3, 4 can then be moved apart with cylinders 6, wherein rod or tube 7 is released.

The operation of the urging means is further elucidated with reference to fig. 2, which shows a preferred embodiment.

Fig. 2 shows the co-acting engaging elements 11 of the opposing parts of the two engaging systems. As is clearly shown here, each engaging element 11 is provided with a recess 15 which is provided with additional transverse grooves in order to enable a good firm engagement on rod or tube 7.

As already noted, chain 8 is preferably embodied here as a double chain wherein engaging elements 11 are arranged in each case between these chains. Each chain of the double chain is provided with plates 16 which are connected to engaging elements 11.

Engaging elements 11 lie with their side remote from recess 15 against the urging means, which are provided in this embodiment with guide rollers 17. These guide rollers 17 are arranged in a circuit 18. When a force is thus exerted on engaging elements 11 by pressure block 13 via rollers 17, these latter will on one side roll over the rear side of engaging elements 11 and on the other side over the bottom of the circuit groove located opposite, so that a very slight friction occurs against the relative movement between the engaging elements and pressure block 13.

The force with which engaging elements 11 are pressed against rod or tube 7 depends on the driving by means of driving devices 10.

Fig. 3 shows an alternative embodiment of urging means 12. The force of the pressure block (not shown here) is herein transmitted via bearing mounted rollers 20. These lie with the peripheral surface against the rear side of engaging elements 11 and thus enable pushing of engaging elements 11 in the direction of rod or tube 7, while these can still move in longitudinal direction along urging means 12.

Fig. 4 and 5 show different embodiments of chains for use with the device according to the invention. Each link is provided with protruding plates 16, in which are formed holes 22 on which engaging elements 11 can be arranged.

The device of fig. 1 is light and compact and can be suitably arranged on for instance the lifting means of a tractor in order to enable manoeuvring herewith in suitable manner on the land. Anywhere where it is desired to carry out for instance a soil-drilling test the tractor can lower the device onto the ground, whereafter the rod or tube can be driven into the ground.

Another option for use is depicted in fig. 6. Device 1 is herein accommodated in a hoist frame 30 and on device 1 is constructed a magazine 31 in which rod or tube 7 can be stored in rolled-up form. In order to bring

and keep rod or tube 7 in the rolled-up form, magazine 31 is provided with a number of guide rollers 32. Rod or tube 7 can be driven into the ground from the rolled-up state by device 1 and also pulled therefrom again and
5 returned to the rolled-up state.

It is noted that the invention is not limited to the embodiments shown in the figures. It is thus not necessary to apply two engaging systems. Three or four may also be used. Nor is it necessary for each of the
10 driving systems to have its own drive. One driven driving system can usually suffice, wherein the other driving system(s) co-displace with the driven system. The urging means can also be embodied in different ways. Some possibilities are already shown in the figures. However,
15 the invention is not limited thereto.

The application of the device described here is not limited to soil-drilling tests. The device can for instance also be used in suitable manner for inserting an earth electrode. Another application is in the laying of
20 cables through pipes. The maximum length of a cable which can be arranged through a pipe depends partly on the force with which the cable can be pushed inside the pipe from the entrance thereof. This is usually carried out using manpower. By using a device according to the
25 invention a considerably greater pushing force can be exerted, whereby the piece of cable to be placed through a pipe at one time can be considerably longer.

A further possible application is in the arranging of a bore under a dike body. Using the device a
30 cable can first be placed through the dike body and a drill attached to the end thereof. By driving the drill on one side and pulling it through the dike body with the cable the drill can be arranged in very rapid manner.

CLAIMS

1. Device for driving a rigid elongate element such as a rod or tube in its longitudinal direction, comprising a frame, at least two engaging systems arranged on the frame which each comprise an endless flexible member provided with engaging elements and guide means for guiding each of the endless members, wherein the guide means of each system are arranged such that they define a part of the endless flexible member in which the engaging elements co-act with those in a corresponding co-acting part of another system, and drive means for driving at least one of the endless members.

2. Device as claimed in claim 1, wherein urging means are arranged to urge the co-acting parts toward each other.

3. Device as claimed in claim 1 or 2, wherein the urging means have a stationary disposition in lengthwise direction of the parts.

4. Device as claimed in claim 3, wherein the urging means guide the parts in sliding manner.

5. Device as claimed in claim 3, wherein the urging means comprise guide rollers for the parts.

6. Device as claimed in claim 5, wherein the guide rollers are arranged in a circuit.

7. Device as claimed in any of the foregoing claims, wherein the engaging elements of at least one flexible member are provided with a recess such that the recesses of the engaging elements in the co-acting parts form a channel for receiving the rigid elongate element.

8. Device as claimed in claim 7, wherein the recess is provided with transverse grooves.

9. Device as claimed in any of the foregoing claims, wherein the flexible member comprises at least one chain and each link bears an engaging element.

10. Device as claimed in claim 9, wherein the flexible member comprises two chains lying adjacently at

a mutual distance and the engaging elements are arranged between these chains.

1/4





FIG.1



3/4

FIG. 5




FIG. 4






FIG. 3



INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL 99/00596

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E21B19/22 B66D3/00 E02D1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B B66D E02D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 775 417 A (COUNCIL MALCOLM N) 7 July 1998 (1998-07-07) column 5, line 44-50 column 6, line 47-51 column 10, line 5-9 figures 2,12	1-10
X	US 4 655 291 A (COX DON C) 7 April 1987 (1987-04-07) column 7, line 1-62 figure 3	1-10
X	CA 1 190 851 A (DYER EQUIPMENT MANUFACTURING LT) 23 July 1985 (1985-07-23) page 4, line 11 page 7, line 14 figures 2,4,5	1-9

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

20 December 1999

Date of mailing of the international search report

13/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Schouten, A

INTERNATIONAL SEARCH REPORT

Inte. onal Application No

PCT/NL 99/00596

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 791 719 A (HALLIBURTON ENERGY SERV INC) 27 August 1997 (1997-08-27) figures 2,4 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL 99/00596

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5775417	A	07-07-1998	CA 2203593 A	21-09-1998
US 4655291	A	07-04-1987	CA 1265998 A	20-02-1990
			GB 2180869 A,B	08-04-1987
			SG 65190 G	26-10-1990
CA 1190851	A	23-07-1985	NONE	
EP 0791719	A	27-08-1997	US 5853118 A	29-12-1998
			CA 2197949 A	22-08-1997
			NO 970778 A	25-08-1997